

URIT



**Analizador Hematológico
5 Diff – 60 Test/Hora
Modelo: Urit-5160**

34 parameters

WBC, LYM%, MON%, NEU%, EOS%, BAS%, LYM#, MON#, NEU#, EOS#, BAS#, RBC, HGB, HCT, MCV, MCH, MCHC, RDW_CV, RDW_SD, PLT, MPV, PDW, PCT, P_LCR, P_LCC, RETIC%, RETIC_ABS, IRF

6 research parameters: ALY#, ALY%, LIC#, LIC%, NRBC#, NRBC%

2 histograms for RBC and PLT

2 scatter grams: 5-part differential scatter gram

Eosinophils and Neutrophils scatter gram

Two 3-D stereograms

Principles of operation

WBC/DIFF: flow cytometry, semi-conductor laser light multi-dimensional cell classification

WBC analysis: optical and impedance measurements

RBC/PLT analysis: impedance method

HGB test: cyanide-free reagent colorimetry

Reagent

Diluent, detergent, lyse, sheath, RETIC staining solution

Sampling modes & aspiration volume

Whole blood: 20 μ L, pre-diluent: 20 μ L

Aperture diameter

WBC 100 μ m, RBC/PLT 68 μ m

Throughput

Whole blood: up to 60 samples per hour, pre-diluent: up to 60 samples per hour

Data storage

Up to 200,000 sample results with grams

Alarms

Error messages & pathological flagging

Display

10.4-inch color touch screen

Power

AC 100–240V, 50/60Hz, 250VA

Dimension

580 mm (L) \times 750 mm (W) \times 550 mm (H)

Weight

About 35 kg



URIT-5160

- Reticulocyte test: RETIC_ABS, RETIC%, IRF
- 34 parameters, 2 histograms, 2 scatter grams and two 3D stereograms
- Hourly throughput up to 60 samples
- Minimized design of 5-part
- The combination of WIC and WOC for WBC counting
- Impedance method for RBC and PLT counting
- Cyanide free reagent for hemoglobin counting
- On board storage capacity of 200,000 samples with all grams
- Support variety of external color printers
- LIS and HIS available with HL7 protocol





Laser Scatter

- Multi angle scatter separation (MASS)
- Original cell morphology signal
- Stable and long-lasting



Sheath Flow Regulation

- Chemical dye free technology
- Only sheath reagent for WBC 5-diff



Diluting Unit

- Separation system for motors and syringes
- Ceramic syringes
- High precision motors



Electronic and Mechanical Components

- Individual quality control management
- Military level
- 20 years field-proven



2D+3D Grams

- Two 2D histograms: RBC and PLT
- Two 2D scattergrams: 5-part differential
Eosinophil and Neutrophil
- Two 3D multi angle vision grams



Data Management

- On board storage capacity of 200,000 samples with all grams
- Professional data statistics query system



Operation Interface

- Simple touch operate with user friendly illustrated icons
- Handy tool tips
- Unique URIT operation interface like all URIT hematology series



Quality Control Solution

- URIT original QC reagent with multi method as L-J, X, X-R, X-B, etc.
- Third party QC solution available