

URIT



Coagulómetro 2 Canales
Modelo: Urit 600

URIT-600

Coagulation Analyzer

Specifications

Principle: dual-magnetic circuit bead method

Parameters:

PT (Prothrombin Time)

APTT(Activated Partial Thromboplastin Time)

TT(Thrombin Time) FIB(Fibrinogen)

Protein C, Protein S, HEP (High-molecular-weight Heparin),

LMWH(Low-molecular-weight Heparin),

LA(Lupus Anticoagulant),

Thrombin factor II, V, VII, X, VIII, IV, IX, X I, X II etc.

Detector: 2 channels

Incubator: 16 sample positions, 4 reagent positions (tunable incubation time)

Data storage: 500 test results

Display: 5.1" LCD screen

Print: Built in printer & external printer

Input / Output: RS-232port and parallel interface

Ambient: work temperature : 15~35 °C;
relative humidity : ≤80%RH

Power: AC100V~240V, 50/60Hz, 45W

Dimension: 380 mm(W) × 340mm(D) × 130mm(H)

Weight: 5.9 kg



Features

- 2 detectors up to 2 different parameters analysis
- Accurate incubator temperature
- Advanced method to eliminate interference from hemolysis, chyle, icterus, turbidity, plasma viscosity etc.
- Mini-reagent consumption, open reagent system
- Internal thermal printer with reference value range