

FICHA TECNICA DE TURBIDIMETRO PORTATIL DIGITAL EZODO

MODELO: TUB-430

EZODO Portable Turbidity Meter



TUB-430

Specifications

	Turbidity
Range	0 ~ 19.99 NTU
	20.0 ~ 199.9 NTU
	200 ~ 1000 NTU
Resolution	0.01/0.1/1 NTU
Accuracy	± 3% of reading + 1 digit at < 500 NTU
	± 5% of reading + 1 digit at > 500 NTU
Response	< 10 seconds
Operating	0 ~ 50 °C, < 85% RH
Sample	10 ml
Data memory	Storage /recall up to 150 points
Power	DC 1.5V (UM4, AAA) battery x 4 pcs
Dimension	Meter: 70 x 135 x 65 mm
Weight	Meter: 168 g (including battery)

Standard Accessories

Standard solution set, Testing bottle x 2, Battery, Clean cloth, Cup, Distilled water, Manual, Carrying case

Features

- Microprocessor based for fast and accurate measurements.
- Measurement method meet ISO 7027.
- Large LCD 45 x 25 mm display for reading convenient.
- Unit NTU, FTU, EBC are changeable.
- Memory function stores and recalls up to 150 points.
- Low battery alarm and auto shut off after 10 minutes of non use.

